

Battery Maintenance Solutions

CHARGE • TEST • MAINTAIN



INPUT VOLTAGE: 110V AC
OUTPUT VOLTAGE: 12V DC
MAX CHARGING CURRENT: 5A
MAX CHARGING DC CURRENT: 5A
DIMENSIONS: 24.6 L X 19.7 W X 1.5 H
WEIGHT: 5.7 LBS.

CHARGING CABINET
RUGGED HPX TECHNOLOGY
EASY-TO-READ LED DISPLAY
ADJUSTABLE PULSE TECHNOLOGY

Battery Analyzer
Starting/Charging System Tester

GOOD & RECHARGE
12.23V 223SAE

6V 12V
Gel
AGM
Standard

390 PT

Automatic
Temperature
Compensation

SolarPULSE
Works with ALL 12-Volt
Lead-Acid Batteries
5 WATTS
350mA

12 VOLT MAINTENANCE
Status
In (Green)
Pulsing (Yellow)
Pulsing (Yellow)
Pulsing (Yellow)
Charging (Green)
Battery
100% (Green)
75% (Yellow)
50% (Orange)
25% (Red)
Test (Red)
No Connection (Red)
Bad Battery (Red)
xtreme CHARGE™
WARNING

PATENTED PULSE TECHNIQUE
INTELLIGENT CIRCUITRY
PROPRIETARY ALGORITHM
800-580-7554 | www.xtremecharge.com
QUICK-DISCONNECT CABLES
FUSE-PROTECTED
BAD BATTERY INDICATOR

